

WHAT IS CLAIMED IS:

1. A shadow mask comprising:

a mask body including a substantially rectangular effective area having a minor axis and a major axis extending at right angles to each other; and

a large number of electron beam passage apertures formed in the effective area,

each of the electron beam passage apertures being formed of a communication hole connecting a larger hole opening in one surface of the effective area and a smaller hole opening in the other surface of the effective area,

in a cross section of the mask body in the major axis direction, a joint portion between the larger and smaller holes of each of at least the electron beam passage apertures in the central portion of the effective area being situated in a central portion in the thickness-direction of the mask body,

in a cross section of the mask body in the major axis direction, a joint portion between the larger and smaller holes of each of the electron beam passage apertures located on the major axis and in the peripheral portion of the effective area being situated closer to one of the surface sides of the effective area than the joint portion of each of the electron beam passages apertures in the central portion of the effective area, the larger hole being offset against

Sub
a' ✓

10015625-121701

*a
conced*

the smaller hole in the ~~direction~~ of the major axis.

2. A shadow mask according to claim 1, wherein
said joint portion between the larger and smaller holes
of each of at least the electron beam passage apertures
5 in the central portion of the ~~effective~~ area is
situated within a range of $0.5 \pm 1/6$ in the thickness
direction of the mask body, as compared with the
thickness of the mask body given by 1.

*Sub
Q2*

10 3. A shadow mask according to claim 2, wherein
said joint portion of each of the electron beam passage
apertures in a region between the minor axis of the
effective area and a position at a distance of $2L/3$ in
the major-axis direction from the minor axis is
situated within the range of $0.5 \pm 1/6$ in the thickness
15 direction of the mask body, where L is the length from
the minor axis of the effective area to a major-axis-
direction end thereof, and

said joint portion of each of the electron beam
passage apertures in a region at the distance of $2L/3$
20 or more in the major-axis direction from the minor axis
of the effective area is situated outside the range of
 $0.5 \pm 1/6$ in the thickness direction of the mask body.

4. A color cathode ray tube comprising:

25 an envelope including a substantially rectangular
face panel having a phosphor screen on the inner
surface thereof;

a shadow mask opposed to the phosphor screen; and

a²
cont

an electron gun for emitting electron beams toward the phosphor screen through the shadow mask,

the shadow mask comprising a mask body including:

5 a substantially rectangular effective area having a minor axis and a major axis extending at right angles to each other and a large number of electron beam passage apertures formed in the effective area,

10 each of the electron beam passage apertures being formed of a communication hole connecting a larger hole opening in one surface of the effective area and a smaller hole opening in the other surface of the effective area,

15 in a cross section of the mask body in the major axis direction, a joint portion between the larger and smaller holes of each of at least the electron beam passage apertures in the central portion of the effective area being situated in a central portion in the thickness-direction of the mask body,

20 in a cross section of the mask body in the major axis direction, a joint portion between the larger and smaller holes of each of the electron beam passage apertures located on the major axis and in the peripheral portion of the effective area being situated closer to one of the surface sides of the effective
25 area than the joint portion of each of the electron beam passages apertures in the central portion of the effective area, the larger hole being offset against

10015625-121701

*a 2
corrected*

the smaller hole in the direction of the major axis.

5 5. A color cathode ray tube according to claim 4,
wherein said joint portion between the larger and
smaller holes of each of at least the electron beam
passage apertures in the central portion of the
effective area is situated within a range of $0.5 \pm 1/6$
in the thickness direction of the mask body, as
compared with the thickness of the mask body given
by 1.

*Sub
a 2
corrected*

10 6. A color cathode ray tube according to claim 5,
wherein said joint portion of each of the electron beam
passage apertures in a region between the minor axis of
the effective area and a position at a distance of $2L/3$
in the major-axis direction from the minor axis is
15 situated within the range of $0.5 \pm 1/6$ in the thickness
direction of the mask body, where L is the length from
the minor axis of the effective area to a major-axis-
direction end thereof, and

20 said joint portion of each of the electron beam
passage apertures in a region at the distance of $2L/3$
or more in the major-axis direction from the minor axis
of the effective area is situated outside the range of
 $0.5 \pm 1/6$ in the thickness direction of the mask body.